

FIBERGLASS ENTRY DOOR SLAB · PANEL · HURRICANE IMPACT RATED (HVHZ)

# 1 Panel Shaker Fiberglass Door

32" x 96" nominal (2/8 x 8/0) · Actual slab 31-3/4" x 95" x 1-3/4"

Scan to view this door  
online: current options,  
pricing and install guides



**FIG. 1 ELEVATION AND EDGE VIEW**

Exterior face shown. Drawn to scale; dimensions are actual, in inches.




**FIG. 2 SHAKER EMBOSMENT PROFILE**

105° bevel from the stile face to a recessed flat, 3/8" deep: a crisp, minimal shaker reveal.



## PANEL LAYOUT

|        |                                                                                      |
|--------|--------------------------------------------------------------------------------------|
| Design | One full-height shaker panel                                                         |
| Panels | Molded into the fiberglass skin; sizes on Fig. 1 are to the outer edge of each panel |

## DIMENSIONS

|              |                                                                                      |
|--------------|--------------------------------------------------------------------------------------|
| Nominal size | 32" x 96" (2/8 x 8/0)                                                                |
| Actual slab  | 31-3/4" W x 95" H x 1-3/4" thick                                                     |
| Stiles       | 4-1/4" each side, to the panel field                                                 |
| Rails        | Top 5-1/8" · bottom 9-7/8"                                                           |
| Panels       | 23-1/4" x 80"                                                                        |
| Prehung unit | About 33-1/2" x 97-3/4" (inswing or saddle sill),<br>33-1/2" x 96-3/4" (bumper sill) |

## CONSTRUCTION

|               |                                                                            |
|---------------|----------------------------------------------------------------------------|
| Build         | Impact-rated build, HVHZ approved                                          |
| Stiles        | Full-length 4" LVL lock and hinge stiles,<br>composite PVC edge cap        |
| Rails         | Composite top and bottom rails; bottom rail<br>kerfed for a drive-in sweep |
| Core          | Foamed-in-place polyurethane, 2.2 lb/cu ft                                 |
| Skins         | Compression-molded fiberglass                                              |
| Texture       | White Satin Smooth (paint grade)                                           |
| Panel profile | Shaker: 105° bevel to a recessed flat, 3/8" deep<br>(Fig. 2)               |
| Edges         | Square edge; reversible for left- or right-hand<br>swing                   |

## PERFORMANCE

|                 |                                                                    |
|-----------------|--------------------------------------------------------------------|
| U-factor / SHGC | 0.18 / 0.01 (NFRC 100 / 200)                                       |
| ENERGY STAR 7.0 | Not ENERGY STAR qualified                                          |
| Impact rating   | Large and small missile; HVHZ and wind-borne<br>debris regions     |
| Design pressure | HVHZ (outswing only): ±50 psf. Elsewhere: ±60<br>psf, either swing |
| Fire rating     | Not fire rated                                                     |

*Thermal: NFRC calculated ratings for an opaque premium-build fiberglass panel door. Impact and DP per Florida approvals FL47392 (HVHZ, TAS 201/202/203) and FL47925. HVHZ installs require a Schlage F Series or Kwikset Signature lockset.*

## STANDARD HARDWARE PREPARATION

Ordered as Standard Prep. Blank (no prep) and custom prep to match an existing door are also available.

**FIG. 3 LOCATIONS**

From top of door, exterior view





**FIG. 4 LOCK EDGE DETAIL**

Cutaway at the lock stile



**FIG. 5 HINGE EDGE DETAIL**

Universal prep; top hinge shown, all four match



- ① Composite PVC edge cap on both stiles
- ② Full-length 4" LVL lock and hinge stiles; solid wood behind every bore, mortise and screw
- ③ Foamed-in-place polyurethane core, 2.2 lb/cu ft
- ④ Composite top and bottom rails
- ⑤ (2) 2-1/8" diameter face bores at 2-3/8" backset, 5-1/2" on center
- ⑥ (2) 1" edge bores for deadbolt and latch
- ⑦ Deadbolt and latch face prep: 1" x 2-1/4" x 5/32" deep, 1/4" radius corners
- ⑧ Universal hinge prep: 4" mortise, .100" deep, routed through the full edge with no screw holes, so the slab hangs either hand

### HINGE PREP

|           |                                                                                                 |
|-----------|-------------------------------------------------------------------------------------------------|
| Hinges    | (4) 4" butt hinges, universal prep (no screw holes); 5/8" radius, 1/4" radius or square corners |
| Locations | 6-1/2", 32-1/2", 58-1/2", 84-1/2" from top of door to top of mortise                            |

### LOCK PREP

|              |                                                  |
|--------------|--------------------------------------------------|
| Bore centers | Deadbolt 50-7/8", latch 56-3/8" from top of door |
| Backset      | 2-3/8" standard; 2-3/4" on request               |

## FINISHING

Satin Smooth is paint grade. Clean and dry all surfaces, apply a bonding primer, then a premium exterior acrylic latex paint. **Finish all six sides**, including both edges, top and bottom, promptly after delivery. Very dark colors in direct sun are not recommended.

## TRIMMING

This door is not a trimmable model. If needed, it can be trimmed up to **1/2" off the bottom only**; seal the cut edge and, ideally, cover it with a U-style door sweep. **Do not trim the top or sides**. Trimming a door that is not sold as trimmable voids the warranty, and modified products cannot be returned. Cutting can also void the impact approval.

## PEASE DOORS 20-YEAR LIMITED WARRANTY

Covers the door slab against defects in material and workmanship that make the product unfit for normal use. Valid for products purchased and installed in the USA with original proof of purchase. Requires proper storage, finishing and installation. Not valid when installed behind a storm door.


| Year     | 1    | 2-3 | 4-6 | 7   | 8   | 9   | 10  | 11-20 |
|----------|------|-----|-----|-----|-----|-----|-----|-------|
| Coverage | 100% | 90% | 80% | 70% | 60% | 50% | 40% | 30%   |

Share of replacement cost covered, by year after purchase.  
Full terms and claims: [peasedoors.com/pages/warranty](https://www.peasedoors.com/pages/warranty)

## GLASS CUTOUT OPTIONS

This door can be cut out in our shop to take door glass in any of the sizes below (1 option). Each drawing shows where the cutout sits on this 31-3/4" x 95" slab, exterior face.

 Cutout (glass opening)       Outside of frame (how we size glass on our site)      Dimensions: top of door to top of cutout; edge of door to cutout



**23" x 81"**

Tall Full Lite

Glass 22" x 80"

Frame 24" x 82"

Location 5-1/8" from top; 4-3/8" from each edge

SKU ZCUT-GFL-2381

- **Impact-rated door:** to keep the hurricane impact rating, the cutout must be fitted with hurricane impact rated door glass.
- Sizes are named by the **cutout**. To match glass you already have, measure the **outside of the plastic frame** (dashed outline); it is 1" larger than the cutout each way.
- Cutout locations follow the ODL door glass standard: centered left to right and measured from the top of the door. Cutouts are made in our shop and are not returnable.