

FIBERGLASS ENTRY DOOR SLAB · PANEL · HURRICANE IMPACT RATED (HVHZ)

2 Panel 3/4 Fiberglass Door

34" x 80" nominal (2/10 x 6/8) · Actual slab 33-3/4" x 79" x 1-3/4"

Scan to view this door
online: current options,
pricing and install guides



FIG. 1 ELEVATION AND EDGE VIEW

Exterior face shown. Drawn to scale; dimensions are actual, in inches.





FIG. 2 RAISED PANEL PROFILE

A decorative bead at the stile, a cove down to the panel edge, then a long, shallow slope rises to the raised field. .49" deep, 2.38" wide.



PANEL LAYOUT

Design	Tall raised panel over a short raised panel
Panels	Molded into the fiberglass skin; sizes on Fig. 1 are to the outer edge of each panel

DIMENSIONS

Nominal size	34" x 80" (2/10 x 6/8)
Actual slab	33-3/4" W x 79" H x 1-3/4" thick
Stiles	5-5/16" each side, to the panel field
Rails	Top 5-1/8" · bottom 8-3/4"
Panels	23-1/8" x 49-1/8", 23-1/8" x 12", top to bottom
Prehung unit	About 35-1/2" x 81-3/4" (inswing or saddle sill), 35-1/2" x 80-3/4" (bumper sill)

CONSTRUCTION

Build	Impact-rated build, HVHZ approved
Stiles	Full-length 4" LVL lock and hinge stiles, composite PVC edge cap
Rails	Composite top and bottom rails; bottom rail kerfed for a drive-in sweep
Core	Foamed-in-place polyurethane, 2.2 lb/cu ft
Skins	Compression-molded fiberglass
Texture	White Satin Smooth (paint grade) or Tan Rift Cut woodgrain
Panel profile	Raised panel: bead, cove and sloped bevel, .49" deep (Fig. 2)
Edges	Square edge; reversible for left- or right-hand swing

PERFORMANCE

U-factor / SHGC	0.17 / 0.01 (NFRC 100 / 200)
ENERGY STAR 7.0	All U.S. climate zones
Impact rating	Large and small missile; HVHZ and wind-borne debris regions
Design pressure	HVHZ (outswing only): ±65 psf wood jambs, ±50 psf composite jambs. Elsewhere: Inswing +65 / -70 psf; outswing ±65 psf
Fire rating	Not fire rated

Thermal: NFRC calculated ratings for an opaque premium-build fiberglass panel door. Impact and DP per Florida approvals FL47392 (HVHZ, TAS 201/202/203) and FL47925. HVHZ installs require a Schlage F Series or Kwikset Signature lockset.

STANDARD HARDWARE PREPARATION

Ordered as Standard Prep. Blank (no prep) and custom prep to match an existing door are also available.

FIG. 3 LOCATIONS

From top of door, exterior view





FIG. 4 LOCK EDGE DETAIL

Cutaway at the lock stile



FIG. 5 HINGE EDGE DETAIL

Universal prep; top hinge shown, all three match



- ① Composite PVC edge cap on both stiles
- ② Full-length 4" LVL lock and hinge stiles; solid wood behind every bore, mortise and screw
- ③ Foamed-in-place polyurethane core, 2.2 lb/cu ft
- ④ Composite top and bottom rails
- ⑤ (2) 2-1/8" diameter face bores at 2-3/8" backset, 5-1/2" on center
- ⑥ (2) 1" edge bores for deadbolt and latch
- ⑦ Deadbolt and latch face prep: 1" x 2-1/4" x 5/32" deep, 1/4" radius corners
- ⑧ Universal hinge prep: 4" mortise, .100" deep, routed through the full edge with no screw holes, so the slab hangs either hand

HINGE PREP

Hinges	(3) 4" butt hinges, universal prep (no screw holes); 5/8" radius, 1/4" radius or square corners
Locations	6-1/2", 37-1/2", 68-1/2" from top of door to top of mortise

LOCK PREP

Bore centers	Deadbolt 40-3/8", latch 45-7/8" from top of door
Backset	2-3/8" standard; 2-3/4" on request

FINISHING

Satin Smooth: bonding primer, then premium exterior acrylic latex paint. **Rift Cut woodgrain:** gel stain made for fiberglass, then a polyurethane topcoat with UV inhibitor (or paint over a bonding primer). **Finish all six sides** promptly after delivery. Avoid very dark colors in direct sun.

TRIMMING

This door is not a trimmable model. If needed, it can be trimmed up to **1/2" off the bottom only**; seal the cut edge and, ideally, cover it with a U-style door sweep. **Do not trim the top or sides.** Trimming a door that is not sold as trimmable voids the warranty, and modified products cannot be returned. Cutting can also void the impact approval.

PEASE DOORS 20-YEAR LIMITED WARRANTY

Covers the door slab against defects in material and workmanship that make the product unfit for normal use. Valid for products purchased and installed in the USA with original proof of purchase. Requires proper storage, finishing and installation. Not valid when installed behind a storm door.

Year	1	2-3	4-6	7	8	9	10	11-20
Coverage	100%	90%	80%	70%	60%	50%	40%	30%

Share of replacement cost covered, by year after purchase.
Full terms and claims: [peasedoors.com/pages/warranty](https://www.peasedoors.com/pages/warranty)

GLASS CUTOUT OPTIONS

This door can be cut out in our shop to take door glass in any of the sizes below (3 options). Each drawing shows where the cutout sits on this 33-3/4" x 79" slab, exterior face.

Cutout (glass opening)

Outside of frame (how we size glass on our site)

Dimensions: top of door to top of cutout; edge of door to cutout

5-1/8"

5-3/8"

23" x 65"

Full Lite

Glass 22" x 64"

Frame 24" x 66"

Location 5-1/8" from top; 5-3/8" from each edge

SKU ZCUT-GFL-2365

5-1/8"

5-3/8"

23" x 49"

3/4 Lite

Glass 22" x 48"

Frame 24" x 50"

Location 5-1/8" from top; 5-3/8" from each edge

SKU ZCUT-G34-2349

9-11/16"

8-7/8"

16" x 40"

Medium Oval

Glass 15-1/2" x 39-3/8" oval

Frame 17.5" x 41.4"

Location 9-11/16" from top; centered in the upper panel

SKU ZCUT-VAL-MD

- **Impact-rated door:** to keep the hurricane impact rating, the cutout must be fitted with hurricane impact rated door glass.
- Sizes are named by the **cutout**. To match glass you already have, measure the **outside of the plastic frame** (dashed outline); it is 1" larger than the cutout each way.
- Cutout locations follow the ODL door glass standard: centered left to right and measured from the top of the door. Cutouts are made in our shop and are not returnable.

Pease Doors · peasedoors.com · (513) 871-8907

2 Panel 3/4 Fiberglass Door 34" x 80" (HVHZ) · Page 3 of 3

34" x 80" is the nominal trade size; all dimensions shown are actual. Specifications are subject to change without notice. Verify local code requirements before installation.