

FIBERGLASS SIDELITE PANEL · FLUSH GLAZED · STANDARD BUILD

Scan to view this sidelite
online: current options,
pricing and install guides




5-Lite Grilles Between Glass 3/4 Lite Shaker Sidelite

14" x 96" nominal (1/2 x 8/0) · Actual sidelite 13-7/8" x 95" x 1-3/4"

FIG. 1 ELEVATION AND EDGE VIEW

Exterior face. To scale; actual inches.



DIMENSIONS


Nominal size	14" x 96" (1/2 x 8/0)
Actual sidelite	13-7/8" W x 95" H x 1-3/4" thick
Stiles	3-3/8" each side, to the lite field
Rails	Top 6" · bottom 9-7/8"
Lite opening	7-1/8" x 63-1/8"
Lower panel	7-1/8" x 12"
In a unit	Pairs with 97-3/4" leg jambs (inswing or saddle sill) or 96-3/4" (bumper sill); same height as the door

CONSTRUCTION

Build	Standard build
Stiles	LVL stiles with composite PVC edge caps
Rails	Composite top and bottom rails
Core	Foamed-in-place polyurethane, 2.2 lb/cu ft
Skins	Compression-molded fiberglass
Texture	White Satin Smooth (paint grade)
Panel profile	Shaker: 105° bevel to a recessed flat, 3/8" deep (Fig. 2)
Edges	Square edge; fixed panel, no hinge or lock prep

FIG. 2 SHAKER EMBOSSMENT PROFILE

105° bevel from the stile face to a recessed flat, 3/8" deep: a crisp, minimal shaker reveal.



PERFORMANCE

U-factor / SHGC	0.24 / 0.07 (NFRC 100 / 200)
ENERGY STAR 7.0	Not ENERGY STAR qualified
Sound (STC)	26 (ASTM E90 / E413)
Design pressure	±50 psf in a door-and-sidelite unit, inswing or outswing
Impact rating	Not impact rated
Fire rating	Not fire rated
Glass	25,000 slam cycles; IG certified to ASTM E2190

Thermal: NFRC calculated ratings, flush glazed Low-E glass with grilles, 411 to 900 sq in glass class. STC from third-party testing of the glass type. Design pressure per Florida Product Approval FL47925 (non-impact).


GLASS

Glass size	8" x 64"; daylight 6-7/8" x 62-7/8"
Unit	Flush glazed, no frame; 1" insulated, tempered both panes; Low-E 366
Design	5-lite grid (1 x 5) of white or black 5/8" or 7/8" grilles sealed between the panes. Privacy: none

CONSTRUCTION AND INSTALLATION

FIG. 3 CONSTRUCTION DETAIL

Cutaway at the top corner



- ① Composite PVC edge cap
- ② LVL stile
- ③ Composite top and bottom rails
- ④ Glass, flush glazed into the panel

INSTALLATION

Sidelite panels are fixed and have no hinge or lock prep. Install alongside a door slab of the same height, assembled into one frame with 97-3/4" leg jambs (inswing or saddle sill). Step-by-step guides are on the product page (scan the QR code).

FINISHING

Satin Smooth is paint grade. Clean and dry all surfaces, apply a bonding primer, then a premium exterior acrylic latex paint. **Finish all six sides**, including both edges, top and bottom, promptly after delivery. Very dark colors in direct sun are not recommended.

TRIMMING

This sidelite is not a trimmable model. If needed, it can be trimmed up to **1/2" off the bottom only**; seal the cut edge. **Do not trim the top or sides**. Trimming a product that is not sold as trimmable voids the warranty, and modified products cannot be returned.

PEASE DOORS 20-YEAR LIMITED WARRANTY

Covers the sidelite panel and its glass against defects in material and workmanship that make the product unfit for normal use. Valid for products purchased and installed in the USA with original proof of purchase. Requires proper storage, finishing and installation. Not valid when installed behind a storm door.

Year	1	2-3	4-6	7	8	9	10	11-20
Coverage	100%	90%	80%	70%	60%	50%	40%	30%

*Share of replacement cost covered, by year after purchase.
Full terms and claims: [peasedoors.com/pages/warranty](https://www.peasedoors.com/pages/warranty)*